

## The Original Marine-Grade Polymer Sheet

King StarBoard<sup>®</sup> is the original marine-grade high-density polyethylene sheet and the leading brand in the marine industry. The King name is synonymous with quality to those who know plastics, and the King StarBoard<sup>®</sup> brand has been helping pros build better boats for more than thirty-years. It is the product of a proprietary process called K-Stran<sup>™</sup>, the most advanced manufacturing process for superior flatness and consistency. King StarBoard<sup>®</sup> has a matte finish on both sides of the sheet. It is environmentally stabilized to withstand the harshest outdoor conditions. King StarBoard<sup>®</sup> will not rust, delaminate or rot when exposed to UV, humidity or water. It is ideal for a variety of marine applications from replacing wood, to building boat components and furniture. The polymer sheet never needs painting or refinishing, works like wood, and is easy to fabricate with common woodworking tools and techniques.

King StarBoard<sup>®</sup> is upgradable to King MicroShield<sup>®</sup> with an advanced antimicrobial technology for protecting the product surface against stain and odor causing bacteria, algae and fungi.<sup>\*</sup>

King StarBoard<sup>®</sup> is upgradable with King FlameShield, for ASTM E-84 Class A Flame Compliance and CAN/ULC-S102 for Canadian Compliance.

For more information about King MicroShield<sup>®</sup> and King FlameShield, please visit www.kingplastic.com

### Marine Products





# STARBOARD<sup>®</sup>

#### Applications

- Bow Pulpits
- Countertops
- Frames and Trim
- Furniture
- Grab Rails and Handles
- Hatches and Doors
- Rod and Cup Holders
- Steps and Dock Boxes
- Tray Tables

#### Specifications

#### Standard Colors

| Standard Sheet Sizes   in: 48" x 96"   mm: 1219 mm x 2438 mm                      | 54" x 96"<br>1371.6 mm x 2438 mm |  |  |  |
|---|----------------------------------|--|--|--|
| Only in 1-1/2" gauge, all standard colors available                               | All standard colors available    |  |  |  |
|   |                                  |  |  |  |
| Standard Gauges   in: 1/4" 3/8" 1/2"   mm: 6.4 mm 9.53 mm 12.7 mm                 |                                  |  |  |  |
| Approximate Weight 48" x 96" (only in 1-1/2" gauge)   lbs: 240 lbs   kg: 108.6 kg |                                  |  |  |  |
|   |                                  |  |  |  |
| Approximate Weight 54" x 96"  |                                  |  |  |  |

| lbs: | 45 lbs | 67.5 lbs | 90 lbs | 135 lbs   180 lbs |  |
|------|--------|----------|--------|-------------------|--|
| kg:  | 20 kg  | 31 kg    | 41 kg  | 61 kg   81 kg     |  |

**Tolerance information:** Gauges 1/4" up to  $1-1/2" \pm 5\%$ Length and width plus only at room temperature

Custom sheet sizes, gauges, and colors available

| Black    | Charcoal Gray | Dolphin Gray | Light Gray  |
|----------|---------------|--------------|-------------|
|          |               |              |             |
| Sanshade | Seafoam       | Arctic White | White/White |

Note: Color accuracy can vary considerably on computer monitors and printers. Please consult your distributor for a product sample before making critical color choices. Disclaimer: King MicroShield® may affect color. King FlameShield may affect finish and color.

\*For bacteriostatic, fungistatic, & algistatic properties. This product is exempt from registration under 40 CFR 152.25(a). King MicroShield® effectiveness verified by ISO and ASTM standards. This product does not protect users or others from disease-causing bacteria. Always clean this product thoroughly after use.

| Properties                        | Units                    | ASTM  | Nominal Values   |
|-----------------------------------|--------------------------|-------|------------------|
| Density                           | g/cc                     | D1505 | 0.955            |
| Tensile Strength @ Yield          | psi                      | D638  | >4,100           |
| Tensile Modulus                   | psi                      | D638  | 255,000          |
| Elongation @ Break                | %                        | D638  | >600             |
| Elongation @ Yield                | %                        | D638  | 9.8              |
| Flexural Modulus                  | psi                      | D790  | 185,000          |
| Flexural Stress @ 5% Strain       | psi                      | D790  | 3,810            |
| Compressive Properties 10% Strain | psi                      | D695  | 4,950            |
| Durometer                         | Shore D                  | D2240 | 68               |
| Tensile Impact                    | ft.lbs./in. <sup>2</sup> | D1822 | 115              |
| Izod Impact Resistance            | ft.lbs./in. <sup>2</sup> | D256  | 1.1              |
| Brittleness Temp.                 | °C (°F)                  | D746  | <-76°C (<-105°F) |
| Vicat Softening Temp.             | °C (°F)                  | D1525 | 123°C (253°F)    |
| Heat Deflection Temp. 66 psi      | °C (°F)                  | D648  | 75°C (167°F)     |
| Screw and Nail Withdrawal         | lbs                      | D1761 | 657 & 63         |
| Flammability                      | Rating                   | UL94  | HB               |

All values are determined on specimens prepared according to ASTM standards.

Nominal values should not be interpreted as specifications.

King StarBoard® is made entirely from FDA and USDA approved material.

King StarBoard® meets ASTM D4976. | The raw material used to make King StarBoard® does not contain BPA's or Phthalates.



King Plastic Corporation

Our Innovation. Your Imagination.®

1100 N. Toledo Blade Blvd. | North Port, FL 34288 USA P: 941.493.5502 | F: 941.497.3274 | www.kingplastic.com

